

HDC

Cutting Fluid

HDC is an industrial-grade, metal working oil. A special blend of powerful lubricants, friction reducers and extreme pressure additives provides excellent lubrication. HDC is equally suited to ferrous metals, stainless and heat resistant steels.

- Industrial grade; allows high-speed punching and extends tool life by reducing the risk of pulling
- Can be used for threading, piercing and screw-cutting
- Suitable for a variety of metals; ideal for the profiling of steel strips
- Suitable for drawing work, cutting and perforation

<u>Description</u>	<u>Packaging</u>	<u>Order Code</u>	<u>Shelf Life</u>
Cutting Fluid	400 ml aerosol	HDC400	48 Months

Directions for Use

Shake the aerosol well before use. Using the extension tube, spray directly onto the surface to be lubricated. Repeat the process if necessary.

Revision 1: Apr 2014

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way,
Ashby de la Zouch,
Leicestershire LE65 1JR
T +44 (0)1530 419 600
F +44 (0)1530 416 640
BS EN ISO 9001:2008
Certificate No. FM 32082